

## SnowDogg® MD68II Snow Plow

Buyers Part Number: MD68II

Full-size power and features in a package optimized for 1/2 ton trucks like the Ford® F-150, Chevy® Silverado 1500, and RAM® 1500

- Redefine what your 1/2 ton truck can do.
- The corrosion resistant 304 stainless steel moldboard never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Full-length 1-3/8 in. cross tube • Six 3/16 in. laser-cut steel ribs • 3/8 in. steel cutting edge
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- Mount and dismount in record time with the new RapidLink™ Attachment System. • Center-mounted drop foot props up your plow with the pull of a handle • Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle • Connects to your truck with a single driver's side foot pedal • Works with all existing SnowDogg MD / VMD truck mounts.
- Two stress-optimized trip springs protect your equipment from hidden curbs and obstacles.
- From the municipal style chain lift to the fully enclosed hydraulic power unit, the MDII handles whatever winter throws at you. • 1/4 in. grade 50 steel construction • Powerful lift cylinders • Over-sized 1-1/2 in. angle cylinders • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses • Optimized hose routing
- Intuitive in-cab controls are simple to use even with gloves on. The backlit one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Contoured poly snow deflector • Cast shoes • Wire reinforced blade guides



## Specifications

<b>Angle Cylinders</b>	1 1/2 x 10"	<b>Angled Blade Width</b>	70.0"
<b>Blade Height</b>	24"	<b>Blade Width</b>	80"
<b>Cutting Edge</b>	3/8 x 6"	<b>Electrical</b>	Headlamp Rated Replaceable Micro-ISO Relays
<b>Harnesses</b>	Separate Light and Hydraulic 4GA Power Wires	<b>Lift Cylinder</b>	1 1/2 x 6"
<b>Lights</b>	Dual Halogen Bulbs or Illuminator™ Heated LEDs	<b>Moldboard Material</b>	304 Stainless Steel
<b>Moldboard Thickness</b>	14 Ga	<b>Mounting System</b>	RapidLink™
<b>Plow Shoes</b>	Standard	<b>Plow Type</b>	Straight Blade
<b>Ribs</b>	6	<b>Snow Deflector</b>	Contoured Poly
<b>Stand</b>	Drop Foot	<b>Trip Springs</b>	2
<b>Trip Style</b>	Full Trip	<b>Shipping Weight</b>	380 lb

WHERE TO BUY