

## SnowDogg® CM110II Snow Plow

**Buyers Part Number:** CM110II

Buyers Products SnowDogg CM Snow Plow is a municipal-grade plow that's weight-optimized for medium duty trucks.

- The corrosion resistant 304 stainless steel moldboard stands 31 in. high and never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Eight 1/4 in. laser-cut vertical steel ribs • Two reinforcing diagonal ribs • Full length 2 in. cross tube • 5/8 in. cutting edge
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- Mount and dismount in one minute or less with the new RapidLink™ Attachment System. • Center-mounted drop foot props up your plow on any surface with the pull of a handle • Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle • Connects to your truck with a single driver side foot pedal
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- Six stress-optimized trip springs protect your equipment from hidden curbs and obstacles.
- From the heavy duty lift cylinder and massive sector to the fully enclosed hydraulic power unit, the SnowDogg CM is built to endure whatever winter throws at you. • Powerful 2 in. lift cylinders • Over-sized 2 in. angle cylinders • Massive 4 in. quadrant • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses
- Intuitive in-cab controls are simple to use even with gloves on. The one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Heavy duty belted rubber snow deflector • Cast shoes • Wire reinforced blade guides

## Specifications

|                            |                                                |                           |                                             |
|----------------------------|------------------------------------------------|---------------------------|---------------------------------------------|
| <b>Angle Cylinders</b>     | 2 x 12"                                        | <b>Angled Blade Width</b> | 116.0"                                      |
| <b>Blade Height</b>        | 31"                                            | <b>Blade Width</b>        | 132"                                        |
| <b>Cutting Edge</b>        | 5/8 x 6 "                                      | <b>Electrical</b>         | Headlamp Rated Replaceable Micro-ISO Relays |
| <b>Harnesses</b>           | Separate Light and Hydraulic 4GA Power Wires   | <b>Lift Cylinder</b>      | 2 x 6"                                      |
| <b>Lights</b>              | Dual Halogen Bulbs or Illuminator™ Heated LEDs | <b>Moldboard Material</b> | 304 Stainless Steel                         |
| <b>Moldboard Thickness</b> | 12 Ga                                          | <b>Mounting System</b>    | RapidLink™ Attachment System                |
| <b>Plow Shoes</b>          | Standard                                       | <b>Plow Type</b>          | Straight Blade                              |
| <b>Ribs</b>                | 10 / 2 Diagonal                                | <b>Snow Deflector</b>     | 3/8 Belted Rubber                           |
| <b>Stand</b>               | Drop Leg                                       | <b>Trip Springs</b>       | 6                                           |
| <b>Trip Style</b>          | Full Trip                                      | <b>Shipping Weight</b>    | 1124 lb                                     |

WHERE TO BUY