

SnowDogg® CM90II Snow Plow

Buyers Part Number: CM90II

Buyers Products SnowDogg CM Snow Plow is a municipal-grade plow that's weight-optimized for medium duty trucks.

- The corrosion resistant 304 stainless steel moldboard stands 31 in. high and never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Eight 1/4 in. laser-cut vertical steel ribs • Two reinforcing diagonal ribs • Full length 2 in. cross tube • 5/8 in. cutting edge
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- Mount and dismount in one minute or less with the new RapidLink™ Attachment System. • Center-mounted drop foot props up your plow on any surface with the pull of a handle • Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle • Connects to your truck with a single driver side foot pedal
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- Six stress-optimized trip springs protect your equipment from hidden curbs and obstacles.
- From the heavy duty lift cylinder and massive sector to the fully enclosed hydraulic power unit, the SnowDogg CM is built to endure whatever winter throws at you. • Powerful 2 in. lift cylinders • Over-sized 2 in. angle cylinders • Massive 4 in. quadrant • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses
- Intuitive in-cab controls are simple to use even with gloves on. The one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Heavy duty belted rubber snow deflector • Cast shoes • Wire reinforced blade guides

Specifications

Angle Cylinders	2 x 12"	Angled Blade Width	92.0"
Blade Height	31"	Blade Width	108"
Cutting Edge	5/8 x 6 "	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	2 x 6"
Lights	Dual Halogen Bulbs or Illuminator™ Heated LEDs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	12 Ga	Mounting System	RapidLink™ Attachment System
Plow Shoes	Standard	Plow Type	Straight Blade
Ribs	10 / 2 Diagonal	Snow Deflector	3/8 Belted Rubber
Stand	Drop Leg	Trip Springs	6
Trip Style	Full Trip	Shipping Weight	1060 lb

WHERE TO BUY