

SnowDogg® VMX75II Snow Plow

Buyers Part Number: VMXII75

A flexible and versatile V-plow optimized for 1/2 ton trucks like the Ford® F-150. Intuitive one-handed controls and double-acting back drag cylinders make the VMXII a powerful winter weapon.

- V PLOW versatility for light duty trucks. The ideal snow plow for trucks like the Ford® F-150, RAM® 1500, and GMC®/Chevy® 1500.
- The corrosion resistant 304 stainless steel moldboards never need painted. A robust frame spreads impact across the flared wings to reduce wear on vital components.
- Three laser-cut steel ribs reinforce each wing.
- Full length 1-3/4 in. cross tubes and heavy duty channels.
- Aggressive 70° attack angle.
- 3/8 in. cutting edge.
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for an efficient scrape. Outstanding performance at any mounting height.
- Each wing has an independent 6 in. trip edge. This protects your equipment from hidden curbs and obstacles without dumping the snow you're pushing.
- Double acting angle cylinders make it easy to put snow where you want it. Back drag with confidence, even in tight spaces.
- From the heavy duty lift cylinder to the fully enclosed hydraulic power unit, SnowDogg plows are built to endure whatever winter throws at you. The revolutionary lift frame design provides sun-parallel stacking power.
- 3/16 in. grade 50 steel construction
- Powerful lift cylinder • Over-sized 1-1/2 in. angle cylinders
- Fully enclosed 2 HP hydraulic power unit



- SAE standard cartridge valves and hefty 3/8 in. rubber hoses
- Optimized hose routing
- Intuitive in-cab controls are simple to use even with gloves on. The backlit controller lets you effortlessly control the V, scoop, and angle functions. Other standard accessories:
- Contoured poly snow deflector
- Wire reinforced blade guides
- How to mount and dismount with some in depth technical features.

Specifications

Angle Cylinders	1 1/2 x 1 3/4 x 12	Angled Blade Width	78.0"
Blade Height	26"	Blade Width	90"
Cutting Edge	3/8 x 6"	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	1 1/2 x 6"
Lights	Dual Halogen Bulbs or Illuminator Heated LEDs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	14 Ga	Mounting System	RapidLink™
Plow Shoes	Optional	Plow Type	V Plow
Ribs	6	Snow Deflector	Contoured Poly
Stand	Drop Foot	Trip Springs	2
Trip Style	Trip Edge	Shipping Weight	530 lb

WHERE TO BUY